

## OMNITRONIC WCS-800 Conference system

8-channel UHF conference system

Art.n.: 80800001

GTIN: 4026397325348



L'articolo non è più disponibile.

### Features :

- Set includes receiver and 8 microphones with built-in transmitter
- Receiver:
  - Diversity system with two removable antennas (BNC connection)
  - Operation in the low-interference UHF-band (740-764 MHz)
  - 8 channels with separate level control and LEDs for carrier and audio signals
  - Balanced XLR output per channel
  - 6.3 mm output for mixed signal
  - Operation via supplied power unit
- Incl. mounting brackets for 483 mm rack installation (1 U)
- Microphones:
  - Dynamic microphone capsule with cardioid characteristic in aluminum diecast housing
  - Operation via supplied 1.5 V batteries (type AA)

#### Dotazione della fornitura

- 1 x microfono

### Logistica

EAN / GTIN: 4026397325348

Peso : 11,20 kg

Lunghezza : 0.56 m

Larghezza : 0.48 m

Altezza : 0.17 m

### Dati tecnici :

Potenza totale installata: 5,00 W

Misure: Larghezza: 28 cm  
Profondità: 21,2 cm  
Altezza: 4,4 cm

Peso: 8,00 kg

|                          |                                                       |
|--------------------------|-------------------------------------------------------|
| Pila:                    | 16 x 1.5 V AA Mignon LR06 alkaline manganese presente |
| System:                  |                                                       |
| Carrier frequency:       | UHF 740-764 MHz                                       |
| Coverage:                | 40 m (with line-of-sight)                             |
| Frequency range:         | 60-16000 Hz ( $\pm 3$ dB)                             |
| T.H.D.:                  | <1%                                                   |
| Dynamic range:           | 90 dBA                                                |
| Receiver:                |                                                       |
| System:                  | Diversity, 8 channels                                 |
| Max. audio output level: | -18 dBV/ 3000 ohms (6.3 mm jack)                      |
|                          | -12 dBV/ 600 ohms (XLR)                               |
| Output impedance:        | 1 kohms (6.3 mm jack)                                 |
|                          | 200 ohms (XLR)                                        |
| Sensitivity:             | <-92 dB                                               |
| Power supply:            | 15-18 V DC, 1000 mA (receiver)                        |
|                          | 230 V AC, 50 Hz (power supply unit)                   |
| Dimensions (H x W x D):  | 280 x 212 x 44 mm                                     |
| Microphone:              |                                                       |
| Polar pattern:           | Cardioid                                              |
| RF power output:         | 10 mW                                                 |
| Max. audio input level:  | 0 dBV                                                 |
| Power supply:            | 1.5 V mignon battery, type AA                         |
| Battery life:            | 8 hours (Alkaline)                                    |
| Dimensions (H x W x D):  | 50 x 111 x 148 mm                                     |